

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

Version:1.00

Revision date: 2023/03/30

Issue date: 2023/03/30

Supersedes:

SECTION 1 Chemical product and company identification

Product identifier

Product form	Article
Name	Li-Ion Battery 16S3P ANR26650 for FX 3-A tool
Product code	BU Direct Fastening
Chemical Chinese name	
Chemical English name	
Recommended use of the chemical	For professional use only Electrical batteries and accumulators

Details of the supplier of the safety data sheet

Supplier Hilti (China) Ltd. 8F, Tower 2, No.58 Yao Yuan Rd. Pudong District 200126 Shanghai - China T +86 21 6016 7316	Department issuing data specification sheet Hilti Entwicklungsgesellschaft mbH Hiltistraße 6 86916 Kaufering - Deutschland T +49 8191 906876 anchor.hse@hilti.com
--	---

Emergency telephone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum - 24h Service +41 44 251 51 51 (international)
------------------	--

Country	Organisation/Company	Address	Emergency number
China	中国境内化学事故应急咨询电话 / chemical accident emergency consultation service hotline (24/7)		+86 532 83889090

SECTION 2 Hazards identification

Emergency overview

Treat symptomatically. Grey. Direct sunlight. Extremely high or low temperatures. Water, humidity. fume. Carbon monoxide. Carbon dioxide. Conductive materials, water, seawater, strong oxidizers and strong acids. Dust/Mist. Heating may cause a fire or explosion. Ventilate area. Equip cleanup crew with proper protection. Risk of explosion by shock, friction, fire or other sources of ignition.

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

GHS hazard classification

Other hazards not mentioned above are Not applicable or No data is available.

Label elements

No data available

Physical and chemical hazards

No additional information available

Health hazards

Symptoms/effects Not expected to present a significant hazard under anticipated conditions of normal use

Environmental hazards

No additional information available

Other hazards

For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand Temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately.

However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be breaked at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

SECTION 3 Composition/information on ingredients

Product form

Article.

Comments

Lithium Ion rechargeable battery pack:

Name/Type	Energy content (Wh).
16S3P ANR26650	396.

This product contains a positive electrode (Lithium iron phosphate), a negative electrode (graphite), electrolyte and binder.

The physical form of the product, however, precludes exposure to workers under normal conditions of use.

This mixture does not contain any substance to be mentioned according to the criteria of section 3 of GB/T 17519-2013

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

SECTION 4 First-aid measures

Description of necessary first-aid measures

First-aid measures general	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.
First-aid measures after inhalation	Allow affected person to breathe fresh air. Allow the victim to rest. If necessary seek medical advice
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention

Most important symptoms/effects

Symptoms/effects	Not expected to present a significant hazard under anticipated conditions of normal use
------------------	---

Advices for first aid responders

No additional information available

Notes for the doctor

Other medical advice or treatment	Treat symptomatically
-----------------------------------	-----------------------

SECTION 5 Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Cool batteries and accumulators with water jet In case of fire in the surroundings: Use extinguishing agent suitable for surrounding fire
Unsuitable extinguishing media	No additional information available

Specific hazards

Fire hazard	Water may not extinguish burning batteries but will cool adjacent batteries and control the spread of fire. Burning batteries will burn themselves out. Virtually all fires involving lithium batteries can be controlled by flooding with water. However, the contents of the battery will react with water and form hydrogen gas. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended.
-------------	--

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

Hazardous decomposition products in case of fire	Formation of toxic gases is possible during heating or in case of fire. Water might react with released Lithium hexafluorophosphate to highly toxic gaseous hydrogen fluoride.
--	---

Advice for firefighters and protective measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Use a self-contained breathing apparatus and also a protective suit

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures	No flames, no sparks. Eliminate all sources of ignition Isolate from fire, if possible, without unnecessary risk
Personal Precautions, Protective Equipment and Emergency Procedures	No additional information available

For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel
----------------------	--------------------------------

For emergency responders

Protective equipment	Equip cleanup crew with proper protection
Emergency procedures	Ventilate area

Environmental precautions

Prevent entry to sewers and public waters	
Notify authorities if liquid enters sewers or public waters	

Methods and material for containment and cleaning up

Methods for cleaning	No additional information available
For containment	No additional information available

Prevention measures for secondary accidents

Prevention Measures for Secondary Accidents	No additional information available
Other information	Dispose of materials or solid residues at an authorized site

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

SECTION 7 Handling and storage

Handling

<p>Precautions for safe handling</p>	<p>Do not soak in water or seawater. Do not expose to strong oxidizers. Do not give a strong mechanical shock or fling. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.</p> <p>Do not throw into fire or expose to high temperatures (>85 ° C). Do not connect the positive terminal to the negative terminal with electrically conductive material. Charge within limits of 0° C to 45° C temperature. Discharge within limits of -20° C to +60° C temperature.</p>
<p>Hygiene measures</p>	<p>Always wash hands after handling the product</p>
<p>Local and general ventilation</p>	<p>No additional information available</p>
<p>Additional hazards when processed</p>	<p>Normal use of this product shall imply use in accordance with the instructions on the packaging and in line with the expectations of a professional user</p>

Storage

<p>Storage conditions</p>	<p>Protect from heat and direct sunlight Protect from moisture.</p>
<p>Material used in packaging/containers</p>	<p>No additional information available</p>
<p>Incompatible products</p>	<p>Strong bases. Strong acids.</p>
<p>Incompatible materials</p>	<p>Sources of ignition. Direct sunlight.</p>
<p>Storage temperature</p>	<p>-20 - 45 ° C (humidity: 0% - 80%)</p>
<p>Information on mixed storage</p>	<p>Store away from water. Do not store together with electrically conductive materials.</p> <p>The accu-pack should be stored at 30 to 50% of the charging capacity. Avoid storing in places where it is exposed to static electricity.</p>
<p>Storage area</p>	<p>Store in a well-ventilated place.</p>

SECTION 8 Exposure controls / Personal protection equipment

Occupational exposure limits

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool	
China - Occupational Exposure Limits	
Local name	乙酸乙酯 # Ethyl acetate
OEL PC-TWA	200 mg/m ³
OEL PC-STEL	300 mg/m ³

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

Regulatory reference	GBZ 2.1-2019
----------------------	--------------

Biological limit values

No additional information available

Monitoring methods

No additional information available

Appropriate engineering controls

Ensure adequate ventilation
If the electrolyte is
leaking out of the battery
pack, the following measures
have to be taken.

Personal protective equipment

Personal protective equipment	Avoid all unnecessary exposure
Other information	Do not eat, drink or smoke when using this product. No additional information available
Hand protection	Wear protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves.	Nitrile rubber (NBR).	6 (> 480 minutes).	0,12		EN ISO 374.

Eye protection	Chemical goggles or safety glasses
Skin and body protection	No additional information available
Respiratory protection	No additional information available
Personal protective equipment symbol(s)	



SECTION 9 Physical and chemical properties

Physical state	Solid
Appearance	No data available
Colour	Grey
Odour	No data available
pH	No data available
Melting point	No data available
Freezing point	Not applicable
Boiling point	Not applicable
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	No data available
Flammability	Non flammable.

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

Vapour pressure	No data available
Relative vapour density at 20° C	No data available
Density	No data available
Solubility	No data available
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	Not applicable
Explosive limits (vol %)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Radioactive	No
Explosive properties	Risk of explosion by shock, friction, fire or other sources of ignition.

SECTION 10 Stability and reactivity

Chemical stability	Stable under normal conditions
Reactivity	No additional information available
Possibility of hazardous reactions	Heating may cause a fire or explosion.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures. Water, humidity
Incompatible materials	Conductive materials, water, seawater, strong oxidizers and strong acids.
Hazardous decomposition products	fume Carbon monoxide Carbon dioxide
Other properties	No additional information available

SECTION 11 Toxicological information

Acute toxicity

Acute toxicity (oral)	No data available (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	No data available (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	No data available (Based on available data, the classification criteria are not met)

Skin corrosion/irritation

Skin corrosion/irritation	No data available (Based on available data, the classification criteria are not met)
---------------------------	--

Serious eye damage/eye irritation

Serious eye damage/irritation	No data available (Based on available data, the classification criteria are not met)
-------------------------------	--

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

Respiratory or skin sensitisation

Respiratory or skin sensitisation	No data available (Based on available data, the classification criteria are not met)
-----------------------------------	--

Germ cell mutagenicity

Germ cell mutagenicity	No data available (Based on available data, the classification criteria are not met)
------------------------	--

Carcinogenicity

Carcinogenicity	No data available (Based on available data, the classification criteria are not met)
-----------------	--

Reproductive toxicity

Reproductive toxicity	No data available (Based on available data, the classification criteria are not met)
-----------------------	--

STOT - single exposure

STOT-single exposure	No data available (Based on available data, the classification criteria are not met)
----------------------	--

STOT - repeated exposure

STOT-repeated exposure	No data available (Based on available data, the classification criteria are not met)
------------------------	--

Aspiration hazard

Aspiration hazard	No data available (Based on available data, the classification criteria are not met)
-------------------	--

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Viscosity, kinematic	Not applicable
----------------------	----------------

SECTION 12 Ecological information

Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	No data available (Based on available data, the classification criteria are not met)
--	--

Hazardous to the aquatic environment, long-term (chronic)	No data available (Based on available data, the classification criteria are not met)
---	--

No additional information available

Persistence and degradability

No additional information available

Bioaccumulative potential

No additional information available

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

Mobility in soil

No additional information available

Other adverse effects

Classification procedure (Ozone)	No data available
Other adverse effects	Do not allow battery packs to penetrate the soil. The battery cell may corrode and electrolyte may leak.
Other information	Do not allow battery packs to penetrate the soil. The battery cell may corrode and electrolyte may leak.

SECTION 13 Disposal considerations

Waste treatment methods	No additional information available
Contaminated container and packaging	No additional information available
Additional information	No additional information available
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations Refer to manufacturer/supplier for information on recovery/recycling
Ecology - waste materials	Avoid release to the environment.

SECTION 14 Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3481	UN 3481	UN 3481	UN 3481	UN 3481
14.2. UN proper shipping name				
LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT	Lithium ion batteries contained in equipment	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT
Transport document description				
UN 3481 LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, 9A, (E)	UN 3481 LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, 9	UN 3481 Lithium ion batteries contained in equipment, 9A	UN 3481 LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, 9A	UN 3481 LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, 9A
14.3. Transport hazard class(es)				
9A	9	9A	9A	9A

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M4
Special provisions (ADR)	188, 230, 310, 348, 360, 376, 377, 387, 390, 670
Limited quantities (ADR)	0
Excepted quantities (ADR)	E0
Packing instructions (ADR)	P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
Transport category (ADR)	2
Tunnel restriction code (ADR)	E

Transport by sea

Special provisions (IMDG)	188, 230, 310, 348, 360, 376, 377, 384, 387
Limited quantities (IMDG)	0
Excepted quantities (IMDG)	E0
Packing instructions (IMDG)	P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-I
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW19
Properties and observations (IMDG)	Electrical batteries containing lithium ion encased in a rigid metallic body. Lithium ion batteries may also be shipped in, or packed with, equipment. Electrical lithium batteries may cause fire due to an explosive rupture of the body caused by improper construction or reaction with contaminants.

Air transport

PCA Excepted quantities (IATA)	E0
PCA Limited quantities (IATA)	Forbidden
PCA limited quantity max net quantity (IATA)	Forbidden
PCA packing instructions (IATA)	967
PCA max net quantity (IATA)	5kg

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

CAO packing instructions (IATA)	967
CAO max net quantity (IATA)	35kg
Special provisions (IATA)	A48, A88, A99, A154, A164, A181, A185, A213, A220
ERG code (IATA)	12FZ

Inland waterway transport

Classification code (ADN)	M4
Special provisions (ADN)	188, 230, 310, 348, 360, 376, 377, 387, 390, 670
Limited quantities (ADN)	0
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP
Number of blue cones/lights (ADN)	0

Rail transport

Classification code (RID)	M4
Special provisions (RID)	188, 230, 310, 348, 360, 376, 377, 387, 390, 670
Limited quantities (RID)	0
Excepted quantities (RID)	E0
Packing instructions (RID)	P903, 908, 909, P910, P911, LP903, LP904, LP905, LP906
Transport category (RID)	2
Colis express (express parcels) (RID)	CE2
Hazard identification number (RID)	90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15 Regulatory information

Regulation on the Administration of Precursor Chemicals (Decree 445 of the State Council)

Catalogue of Precursor Chemicals

SECTION 16 Other information

Data sources European Chemicals Agency, <http://echa.europa.eu/> manufacturer

Abbreviations and acronyms	
CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to GB/T 16483 and GB/T 17519

CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
EC50	Median effective concentration
ED	Endocrine disrupting properties
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
N. O. S.	Not Otherwise Specified
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative
NOAEL	No-Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level

Section	Changed item	Change	Comments
1.	Trade name.	Modified.	
14.	Transportation information.	Modified.	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.